

- Zertifikat UL Listed
- CRI 90+
- MacAdam 2-Stufen-Ellipse, einfache Gruppierung




Technische Spezifikation


Model	Versorgungsspannung	Leistung	Lichtfarbe	Ilość LED szt./m	Lichtstrom	Maximale Lieferlänge	Abstrahlwinkel	LED-Breite
K-22-1091-24V	24 V	9.1 W/m	2200 K	196	760 lm/m	3 m	120 °	5 mm
K-25-1091-24V	24 V	9.1 W/m	2500 K	196	816 lm/m	3 m	120 °	5 mm
K-27-1091-24V	24 V	9.1 W/m	2700 K	196	910 lm/m	3 m	120 °	5 mm
K-30-1091-24V	24 V	9.1 W/m	3000 K	196	950 lm/m	3 m	120 °	5 mm
K-35-1091-24V	24 V	9.1 W/m	3500 K	196	990 lm/m	3 m	120 °	5 mm
K-40-1091-24V	24 V	9.1 W/m	4000 K	196	1020 lm/m	3 m	120 °	5 mm
K-50-1091-24V	24 V	9.1 W/m	5000 K	196	1016 lm/m	3 m	120 °	5 mm




VERWANDTE PROFILE




Profil LINO
Ref: B8287



Profil PIKO
Ref: B8288



Profil PIKO-O
Ref: C1167



Profil LIPOD-50
Ref: C2609